



ALUFLAME WORK MOLTEN METAL FR TROUSERS

DESCRIPTION

Developed for the demanding environment of aluminium, iron and steel works, this inherent fabric offers maximum protection.

COMPOSITION

 **Aluflame Work: 43% Cotton, 30% Viscose, 20% Acrylic, 6% Para Aramid, 1% Carbon Fibre, 360360g**
 **Navy S-3XL**

FEATURES

- Highest protection against molten aluminium
- Class 2 welding protection
- Certified protection against molten metal splash
- Rule pocket
- Jetted back pocket
- Extendable leg length (31" to 33")
- Half elasticated waist for a secure and comfortable fit
- 4 pockets for ample storage
- 40+ UPF rated fabric to block 98% of UV rays
- Suitable to be worn in an ATEX environment
- CE-CAT III
- CE certified

STANDARDS

EN ISO 11612 A1+A2, B1, C1, D3, E3, F1
EN ISO 11611 Class 2 A1+A2
EN 1149 -5
IEC 61482-2 IEC 61482-1-1 ELIM 8.1 CAL/CM², ATPV 9.5 CAL/CM²
IEC 61482-2 IEC 61482-1-2 APC 1
ASTM F1959/F1959M-14e1 ATPV=13 Cal/CM² (HAF=84.9%)

COLOUR / SIZES

SKU	COLOUR	SIZE RANGE
FR64NAR	NAVY	S-3XL



STANDARDS



EN ISO 11612
Protective Clothing Against Heat and Flame



EN ISO 11611
Protective clothing for use in welding and allied processes.



EN ISO 1149
Protective Clothing - Electrostatic Properties - Part 5. Material Performance and Design Requirements.



IEC 61482-2
Protective Clothing Against the Thermal Hazards of an Electric Arc

TECHINCAL INFORMATION



SATRA Technology Centre Ltd
(Notified Body Number.: AB: 0321) SATRA
Technology Park Wyndham Way Telford Way
Kettering Northamptonshire NN16 8SD, United
Kingdom Cert No: 2777/25491-01/E00-00

OEKO-TEX® Certificate
Cert Number: 11-25330

Item	Colour Fit	MS Len	MS Wid	MS HGT	MS WGT	MS CC	MS EAN13	MS DUN14
FR64NARS	Navy	59	38	23	.765	2864.777	5036108351992	15036108840615
FR64NARM	Navy	59	38	23	.805	2864.777	5036108351985	15036108840608
FR64NARL	Navy	59	38	23	.839	2864.777	5036108351978	15036108840592
FR64NARXL	Navy	59	38	26	.878	3238.444	5036108352005	15036108840622
FR64NARXXL	Navy	59	38	26	.921	3238.444	5036108352012	15036108840639
FR64NARXXXL	Navy	59	38	26	.957	3238.444	5036108352029	15036108840646